



STANDARD HOISTWAY PLAN

NOTE: ALL DIMENSIONS ARE APPROXIMATE

1. IF PLATFORM SIZE IS REDUCED, THE BLOCKING IS TO BE POSITIONED SUCH THAT IT IS CENTERED ON PLATFORM. (PLATFORM DEPTH /2) + 2" = CENTERLINE OF RAIL BLOCKING OFF OF INSIDE FRONT WALL. (MIN 27" DIMENSION)
2. CAR TO WALL (CTW) DIMENSION IS 3" MIN. WITH WALL MOUNT PHONE AND 4" MIN WITH PHONE BOX.
3. HOISTWAY DOORS AND FRAMES TO BE INSTALLED IN A 2" X 4" WALL CONSTRUCTION TO EQUATE TO A 2" X 4" WALL. THIS IS REQUIRED TO COMPLY WITH THE 3" X 5" RULE.
4. HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS)
5. CLEAR CAB DIMENSIONS BASED ON A 3/4" FLAT WALL CAB DESIGN. PICTURE FRAME AND FRAME/PANEL CABS REDUCE CLEAR INSIDE WIDTH BY 1-1 1/2" AND CLEAR INSIDE DEPTH BY 3/4".

 **SOUTHEASTERN
ELEVATOR**
ELEVATORS & MOBILITY SOLUTIONS

877-720-0075

DRAWING NO.

HYD HP1-12